

**FWA02~12BATN5VE (D/G)**

WA02~12BATN5VE (D/G)				2	3	4	5	6	7	8	10	12
Total Cooling Capacity	HIGH		kW	2,7	2,9	3,4	6,1	6,3	6,4	6,9	9,8	10,1
	MED		kW	1,8	2,7	3,3	4,4	5,4	6,1	6,8	8,4	9,8
	LOW		kW	1,4	1,7	2,1	3,1	4,4	4,4	6,2	7,6	8,4
Sensible Cooling Capacity	HIGH		kW	1,9	2,0	2,3	4,2	4,3	4,4	4,8	6,8	7,0
	MED		kW	1,2	1,9	2,3	3,0	3,7	4,2	4,7	5,8	6,8
	LOW		kW	0,9	1,2	1,4	2,5	3,0	3,0	4,3	5,2	5,8
Power Input	HIGH		W	97	101	108	167	171	178	202	280	283
	MED		W	86	97	107	141	155	167	197	273	280
	LOW		W	76	82	88	127	141	141	191	272	273
Dimension	Unit	Height	mm	253								
		Width	mm	788								
		Depth	mm	819			1284				1734	
Weight	Unit	Unit	kg	23			35				53	
		Packing Unit	kg	27			41				60	
FAN	Type			Sirocco Fan								
	Quantity			1			2				4	
	Air Flow Rate	HIGH	cfm	323	349	417	715	740	762	827	1182	1214
		MED	cfm	214	323	408	492	623	715	808	1056	1182
		LOW	cfm	138	185	226	323	492	492	734	929	1056
Total Sound Power Level	Inlet	HIGH	dBA	56	52	59	62	61	61	61	63	62
		MED	dBA	51	49	52	61	60	59	57	62	61
		LOW	dBA	49	49	52	59	57	54	55	61	59
	Outlet	HIGH	dBA	55	50	58	58	57	57	57	60	60
		MED	dBA	49	47	50	57	57	55	54	60	57
		LOW	dBA	47	47	50	55	54	51	51	57	56
Piping Connections	Water	Inlet		3/4"								
		Outlet		3/4"								
	Drain		mm	3/4 Male								
Power Supply	Type			220-240 / 1 / 50								
	Phase			1~								
	Frequency		Hz	50								
	Voltage		V	220-240								

Data is declared in table conditions below:
 1- On coil : 24 / 18 DB/WB °C

2- Chilled Water Temperature : 14,5 / 5,5 In/Out °C
 3- ESP: 50 Pa

DAIKIN MIDDLE EAST AND AFRICA FZE

P.O. Box 18674, Jebel Ali Free Zone, Dubai, UAE, Tel: +971 (0) 4 815 9300, Fax: +971 (0) 4 815 9311

Email: info@daikinmea.com Web: www.daikinmea.com



Daikin Middle East and Africa



DMEA20-107